

2.5XR 2 Stainless steel body drilling pump



Application

- Pumping for drilling, well, tank
- For domestic (watering, irrigation) or industrial applications

Pompe

- Maximum liquid temperature: +35°C
- Maximum sand content: 0,25%
- Maximum immersion depth: 80 m
- Minimum borehole diameter: 3"
- Curved tolerance in accordance with the standard ISO 9906

Moteur

- Rewindable motor


Identification codes

3	XR	m	3	/11	-0.37	
						Nominal power (kW)
						Number of impeller stages
						Nominal flow (m ³ /h)
						Single phase
						Submersible borehole pump
						Minimum borehole diameter (in ")

Technical data

MODEL	kW	Q (m ³ /h)									
		0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	
		Q (l/min)									
		0	5	10	15	20	25	30	35	40	
2.5XRm2/24-0.37	0.37	65	60	56	52	46	40	33	22	10	
2.5XRm2/31-0.55	0.55	84	77	72	67	60	52	43	29	13	
CONTROLBOX 2,5XRm2/24-0.37KW - 0	0										
CONTROLBOX 2,5XRm2/31-0.55KW - 0	0										

Dimensions



MODEL	DN	P	M	T	poidsP	poidsM	poidsT
2.5XRm2/24-0.37	1	779	787	1546	4.1	8.2	12.3
2.5XRm2/31-0.55	1	993	1001	1994	4.4	8.9	13.3
CONTROLBOX 2,5XRm2/24-0.37KW - 0							
CONTROLBOX 2,5XRm2/31-0.55KW							